

Cable Eléctrico.

Cable Unipolar 105° FLRY-B

Temperatura: -40°C/+105°C

CÓDIGO	SECCIÓN	m/ROLLO	COMPOSICIÓN	PVP/m
CI-0,50	0,50mm	100m	16x0,20/1,5mm	0,3686
CI-0,75	0,75mm	100m	24x0,20/1,8mm	0,4572
CI-1,50	1,50mm	100m	24x0,26/2,3mm	0,6858
CI-2,50	2,50mm	50m	40x0,26/2,9mm	1,2000
CI-4,00	4,00mm	25m	41x0,31/3,5mm	1,9429
CI-6,00	6,00mm	25m	74x0,31/4,2mm	2,8858
PNB-50	2x0,50mm	100m	2x16x0,20	0,4900
PNB-75	2x0,75mm	100m	2x24x0,20	0,6500
PNB-150	2x1,50mm	100m	2x24x0,26	1,0600



CI/CABLE UNIPOLAR



PNB/CABLE PARALELO BICOLOR

CÓDIGO	COLORES
CI-0,50/0,75	AM/AZ/BL/GR/VI/NG/MA/RO/NJ/VE/RS
CI-1,50/2,50	RO/NG
CI-4,00/6,00	RO/NG
PNB-	ROJO-NEGRO

Conductores Eléctricos.

Cable de Arranque Extraflexible

Temperatura: -40°C/+70°C

CÓDIGO	SECCIÓN	ROLLO 5/METROS	ROLLO 15/METROS	ROLLO 25/METROS
		PRECIOS NETOS POR METRO		
CAA-10-NG	10mm	2,65	2,42	2,15
CAA-10-RO	10mm	2,65	2,42	2,15
CAA-16-NG	16mm	3,91	3,62	3,17
CAA-16-RO	16mm	3,91	3,62	3,17
CAA-25-NG	25mm	6,14	5,32	4,99
CAA-25-RO	25mm	6,14	5,32	4,99
CAA-35-NG	35mm	8,68	7,52	7,05
CAA-35-RO	35mm	8,68	7,52	7,05
CAA-50-NG	50mm	12,11	10,48	9,83
CAA-50-RO	50mm	12,11	10,48	9,83



CÓDIGO	SECCIÓN	COLOR	COMPOSICIÓN	EXTENSIÓN
CAA-10-NG/RO	10mm	NEGRO/ROJO	188x0,25	7,90
CAA-16-NG/RO	16mm	NEGRO/ROJO	192x0,31	8,30
CAA-25-NG/RO	25mm	NEGRO/ROJO	300x0,31	10,10
CAA-35-NG/RO	35mm	NEGRO/ROJO	432x0,31	11,80
CAA-50-NG/RO	50mm	NEGRO/ROJO	616x0,31	13,50